


## AquaStar 1000P

## Pilot ignition.

Endless hot water for 1 sink at a time.

## **Features**


- 78% efficient
- Standing pilot
- 12-year warranty on heat exchanger 2 years on parts
- Mounts on wall for easy installation
- Compact and lightweight
- Modulating gas valve to control temperature
- Pressure relief valve included
- CSA approved



Water Flow Control Knob

Technical Specifications	
Power Input	Natural Gas: 30,735 - 74,900 Btu LP Gas: 30,735 - 74,900 Btu
Minimum Flow to Activate	0.5 gallons per minute (gpm)
Flow Rates	45°F rise @ 2.6 gpm 55°F rise @ 2.1 gpm 65°F rise @ 1.7 gpm 77°F rise @ 1.5 gpm 90°F rise @ 1.3 gpm
Energy Factor	.64
Thermal Efficiency	78%
Dimensions	H: 28.8" W: 12.2" D: 8.5"
Weight	25 lbs.
<b>Modulating Gas Valve</b>	Yes
Ignition	Standing Pilot

Installation Specifications		
Gas Connection	½" Male NPT	
Water Connections	½" Male NPT	
Natural Gas Pressure	Minimum: 7" WC Maximum: 14" WC	
Liquid Propane Pressure	Minimum: 11" WC Maximum: 14" WC	
Water Pressure	Minimum: 30 PSI Maximum: 150 PSI	
Electrical Supply	None	
Vent Size	4" (double-wall type B)	
Vent Termination	Vertical	



**BBT** NORTH AMERICA CORPORATION Bosch Group

Bosch Water Heating 340 Mad River Park Waitsfield, VT 05673

866.642.3199 • www.boschhotwater.com