

AquaStar 125FX

Power vented for horizontal venting installations.

Endless hot water for 1 major application at a time.

Features

- Delivers up to 4.6 gallons per minute
- No standing pilot
- Vents horizontally
- 12-year warranty on heat exchanger 2 years on parts
- Provides ENDLESS supply of hot water
- Saves up to 50% off utility costs
- · Can simply hang on the wall
- Modulating gas valve to control temperature
- Pressure relief valve included
- · CSA approved



Stainless Steel Burners

Temperature Control Knob




Natural Gas: 28,000 - 130,000 Btu LP Gas: 28,000 - 125,000 Btu De Gas: 28,000 - 130,000 Btu De Gas: 28,000 - 125,000 Btu De Gas: 28,000 Btu De Gas: 28,000 Btu De Gas: 28,000 Btu De Gas: 28	LP Gas: 28,000 - 125,000 Btu	Technical Specifications		
## 45°F rise @ 4.6 gpm	## ## ## ## ## ## ## ## ## ## ## ## ##	Power Input		
Flow Rates 55°F rise @ 3.8 gpm 65°F rise @ 3.3 gpm 77°F rise @ 2.7 gpm 90°F rise @ 2.3 gpm Energy Factor NG: .78 LP: .81 Thermal Efficiency NG: 80% LP: 82% Dimensions H: 29 ¾" W: 18 ¼" D: 8 ¾" Weight 44 lbs.	Flow Rates 55°F rise @ 3.8 gpm 65°F rise @ 3.3 gpm 77°F rise @ 2.7 gpm 90°F rise @ 2.3 gpm Energy Factor NG: .78 LP: .81 Thermal Efficiency NG: 80% LP: 82% Dimensions H: 29 ¾" W: 18 ¾" D: 8 ¾" Weight 44 lbs. Modulating Gas Valve Ignition Electronic (120V plug included)	Minimum Flow to Activate	0.5 gallons per minute (gpm)	
Thermal Efficiency NG: 80% LP: 82% Dimensions H: 29 ¾" W: 18 ¼" D: 8 ¾" Weight 44 lbs.	Thermal Efficiency NG: 80% LP: 82% Dimensions H: 29 ¾" W: 18 ¾" D: 8 ¾" Weight 44 lbs. Modulating Gas Valve Ignition Electronic (120V plug included)	Flow Rates	55°F rise @ 3.8 gpm 65°F rise @ 3.3 gpm 77°F rise @ 2.7 gpm	
Dimensions H: 29 ¾" W: 18 ¼" D: 8 ¾" Weight 44 lbs.	Dimensions H: 29 ¾" W: 18 ¼" D: 8 ¾" Weight 44 lbs. Modulating Gas Valve Yes Ignition Electronic (120V plug included)	Energy Factor	NG: .78 LP: .81	
Weight 44 lbs.	Weight 44 lbs. Modulating Gas Valve Yes Ignition Electronic (120V plug included)	Thermal Efficiency	NG: 80% LP: 82%	
	Modulating Gas Valve Yes Ignition Electronic (120V plug included)	Dimensions	H: 29 ¾" W: 18 ¼" D: 8 ¾"	
Modulating Gas Valve Yes	Ignition Electronic (120V plug included)	Weight	44 lbs.	
		Modulating Gas Valve	Yes	
Ignition Electronic (120V plug included)	Accessories Vent Terminator (FXHOOD included)	Ignition	Electronic (120V plug included)	
Accessories Vent Terminator (FXHOOD included)		Accessories	Vent Terminator (FXHOOD included)	

Installation Specifications		
Gas Connection	½" Male NPT	
Water Connections	½" Male NPT	
Natural Gas Pressure	Minimum: 7" WC Maximum: 14" WC	
Liquid Propane Pressure	Minimum: 11" WC Maximum: 14" WC	
Water Pressure	Minimum: 30 PSI Maximum: 150 PSI	
Electrical Supply	120 volts / 1.2 amps (plug in)	
Vent Size	4" (single-wall sealed stainless or galvanized)	
Vent Termination	Horizontal w/FXHOOD*	

^{*} FXHOOD required and included with AquaStar 125FX







The Horizontal Vent
Terminator – FXHOOD is
design-approved for the
125FX and has a built-in
back draft flapper to
prevent negative air from
freezing the unit.

BBT NORTH AMERICA CORPORATION Bosch Group

Bosch Water Heating 340 Mad River Park Waitsfield, VT 05673

866.642.3199 · www.boschhotwater.com